

UNCLASSIFIED

AD NUMBER
AD337352
CLASSIFICATION CHANGES
TO: unclassified
FROM: restricted
LIMITATION CHANGES
TO: Approved for public release, distribution unlimited
FROM: Controlling Organization: British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20008.
AUTHORITY
DSTL, ADM 227/1797, 31 Jul 2008; DSTL, ADM 227/1797, 31 Jul 2008

THIS PAGE IS UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION
AFFECTING THE NATIONAL DEFENSE OF
THE UNITED STATES WITHIN THE MEAN-
ING OF THE ESPIONAGE LAWS, TITLE 18,
U.S.C., SECTIONS 793 and 794. THE
TRANSMISSION OR THE REVELATION OF
ITS CONTENTS IN ANY MANNER TO AN
UNAUTHORIZED PERSON IS PROHIBITED
BY LAW.

RESTRICTED ACSIL/ADM/ 53/1102

Report No. 2383/3384/1
Date - 3 APR 1963

U.S. CONFIDENTIAL - Modified Handling Authorized
U.K. RESTRICTED

CLASSIFIED BY DDC
AS AD No. 337352

ELECTRICAL DEPARTMENT
ADMIRALTY ENGINEERING
LABORATORY
WEST DRAYTON, MIDDLESEX

DDC
RECEIVED
JUN 26 1963
TUSA B

HARMONIC RESPONSE TESTER

[U]

337 352

U.S. CONFIDENTIAL - Modified Handling Authorized
U.K. RESTRICTED

EXCLUDED FROM AUTOMATIC
REGRADING: DOD DIR 5200.10
DOES NOT APPLY

Copy No. 9

RESTRICTED

U. S. CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED

This document is the property of Her Majesty's Government. It is for the information of officers and responsible officials. The officer or official in possession of this document will be responsible for its safe custody and for ensuring that its contents are not disclosed to any unauthorised person.

REPORT NO. 2383/3384/1

DATE 3 APR 1963

This document must be kept under lock and key when not in actual use. Any loss or destruction must be reported immediately to the issuing authority through the normal channels.

ELECTRICAL DEPARTMENT

ADMIRALTY ENGINEERING LABORATORY

WEST DRAYTON, MIDDLESEX.

HARMONIC RESPONSE TESTER

Investigators:-

A.W. Blane, A.H-W.C., Graduate I.E.E.
E.C. Tapper, B.Sc.
D.J. Parsons

"This document contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U. S. C., Section 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law."

Head of Section

Approved

R. F. Hickson

Superintending Electrical Engineer

Authorised

[Signature]
Head of Electrical Department
A.E.L.

U. S. CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED
RESTRICTED

RESTRICTED

S U M M A R Y

The development of a portable harmonic response tester for a.c. servo systems is described up to the construction of the laboratory prototype model. The equipment is largely transistorised and provision is made for incorporating a d.c. adaptor, the design of which is discussed, at a later date.

RESTRICTED

RESTRICTED

U.S. CONFIDENTIAL
MODIFIED HANDLED BY AUTHORIZED

HARMONIC RESPONSE TESTER

1. INTRODUCTION

A harmonic response tester for servo systems was developed at the Laboratory in 1954 and 4 models were constructed. The evaluation and use of these instruments for obtaining Nyquist diagrams for weapon-control servo systems showed a number of limitations in their electrical characteristics. In addition the two units comprising the tester were too heavy for easy portability.

A start was made in 1959 to design a transistorised version incorporating a number of refinements. Many difficulties were experienced during the early development, largely because of the limited range of transistors available; as silicon types became available, difficulties due to d.c. drifts were gradually eliminated.

Considerable effort was expended in designing an amplifier suitable for a dual tester (for a.c. and d.c. servo systems) but the required closed-loop gain was 1000 and the versions developed proved insufficiently stable. Eventually it was decided to concentrate on a model suitable for a.c. only, which would cater for the majority of Service systems. The agreed specification for this version is shown in the Appendix, and a general view of the equipment is shown in Fig. 1.

2. BASIC SYSTEM (Fig. 2)

The tester was designed for analysis of servo systems employing a 400 c/s carrier and provision is also made for operation on 1100 c/s supplies (to be tested).

The signal generator section has a maximum output of 10V (peak) into a load of minimum impedance $1\text{ k}\Omega$, and its modulation frequency can be set (in 2 ranges) from 0.15 to 50 c/s. An additional facility gives a frequency sweep from the set frequency to zero. Provision is made for variable reset.

The amplitude and phase measuring section has an input impedance of more than $1\text{ M}\Omega$ with both input and output terminals isolated from earth and each other. A.C. (i.e. modulated carrier) signals only can be accepted. Amplitude is read directly while phase change is obtained by a nulling method.

A stabilised power supply unit provides d.c. rail voltages of +20, 0 and -20V.

3. SIGNAL GENERATOR (Fig. 3)

The signal generator incorporates a gearbox in which two Type 11 CX4b synchros geared 10:1 are driven by a velodyne system. The speed of the velodyne system thus determines the modulation frequency of the 400 c/s signal. Size 18 motor and tachogenerators are used and the gearbox is screened to reduce interference generated by their commutators.

A simple d.c. amplifier provides the drive for the motor, with negative feedback from the tachogenerator. The frequency is set by a logarithmic potentiometer (RV4) which gives good setting control at the low speeds.

U.S. CONFIDENTIAL
MODIFIED HANDLED BY AUTHORIZED
RESTRICTED

/The

RESTRICTED

2.

The maximum frequency of 5 c/s on low range (50 c/s on high range) is preset by feedback adjustment (RV2); the minimum frequency, about 0.15 c/s, is preset by a bias adjustment (RV3).

A frequency sweep which has a choice of two decay times can be selected by SW7.

A switched output transformer provides an output which can be set over the range of 0 to 10V (peak) with an error of less than 1 mV (peak).

4. RESET AMPLIFIER (Fig. 4)

A resetting device can be inserted in series with the generator output to give a variable value of feedback in ranges 0-5%, 5-10%, 10-20%, 20-50% and 50-100%. It is essentially a transformer-coupled amplifier with a push-pull output employing overall feedback for gain control.

5. AMPLITUDE MEASUREMENT (Fig. 5)

The response signals from the servo under analysis are connected to the reset and amplitude amplifiers by a screened unit containing a high-impedance isolating transformer and a double triode with buffer-stage transistors.

The range switch SW8 allows direct reading of signals at ranges 10 mV, 100 mV, 1V and 10V.

The amplitude amplifier is a.c. coupled with considerable local feedback on each stage, the overall voltage gain being adjusted to 1000. Its output is connected through separate demodulating circuits to the amplitude metering circuit and the phase measuring circuit.

The output from the demodulator in the metering circuit is virtually the peak-to-peak value of the modulation which is referred to the base of the first emitter-follower. As the meter is calibrated to measure 20V peak-to-peak and the amplifier overall gain is 1000, the most sensitive f.s.d. is when 20 mV peak-to-peak is applied. Because of diode voltage drops in the demodulator, the smallest signal measurable is 2 mV peak-to-peak, and the scale (marked 0-10V) has the lower portion obliterated.

6. PHASE MEASUREMENT (Fig. 6)

A Type 11 CT4b synchro is included in the phase measuring circuit and the phase of its output may be set by hand to any desired value with respect to the response signal. It is connected to the Type 11 CX4b synchros in the signal generator.

The output of the Type 11 CT4B synchro is fed via a reference transformer to a demodulator summing circuit in which it is added to the error-signal output of the amplitude amplifier. The sum of the voltage is fed to the grids of a pair of electrometer triodes controlling an emitter-pair coupled through a centre-zero microammeter.

When the phase change is nulled correctly the meter needle swings equally about the centre, the frequency and amplitude of swing being dependent on the modulation frequency.

Provision is made for quiescent balance of the electrometer triodes.

/7.

RESTRICTED

RESTRICTED

3.

7. POWER SUPPLY UNIT (Fig. 7)

The power supply circuit is conventional and consists of two linked identical full-wave rectifier circuits fed from a transformer. The 25V supply for the signal generator velodyne is also derived via rectifiers from the same transformer.

The unit also includes switches used for setting up the amplifiers and making pre-operational checks. The mains input switch is contained on a separate chassis (Fig. 3).

8. FIRST LABORATORY PROTOTYPE

The first prototype uses IMHOF modular chassis mounted in two 19 x 7 in. frames bolted together, making the overall size 20 x 16 x 11 in. Most of the transistor circuitry is mounted on VEROBOARD and the units plug into MICROCON sockets.

A further report will describe the use of this unit on various servo systems.

9. SECOND LABORATORY PROTOTYPE

A number of improvements will be made in the design and construction of the second model and may be applied retrospectively to the first.

These include:

- (a) Use of smaller meters which will reduce the width of the amplitude and phase measuring units and the signal generator unit to 4 in.
- (b) Redesign of the gearbox so that the fast-driven synchro is declutched when the signal generator is being used on the low-frequency range. The use of an in-line motor-tachogenerator is also being considered.
- (c) Redesign of the phase indicator to replace the present gearing, dial and geneva wheel mechanism by a counter.

10. D.C. ADAPTOR

Provision is made for the inclusion of a d.c. adaptor in Model 1. It is envisaged that this would take the form of a low-gain d.c. amplifier (chopper-stabilised) followed by a modulator. It would also include a demodulator for the signal generator.

There are considerable difficulties in developing this circuitry and it may be decided that the limited use with d.c. does not justify the over-complication of the tester.

RESTRICTED

RESTRICTED

HARMONIC RESPONSE TESTER

APPENDIX

Specification for Harmonic Response Tester - 115V, 400 c/s Servo Systems

(200V, 1100 c/s systems with minor modifications)

(a) Signal levels	1 mV to 10V peak of carrier
(b) Minimum tester input impedance	> 1 M Ω
(c) Modulation frequency range	0.15 to 5 c/s 5 to 50 c/s
(d) Sweep frequency exponential decay time constants	30 seconds 140 seconds
(e) Minimum load impedance	1 k Ω
(f) Maximum load voltage	10V peak
(g) Accuracy of phase measurement	2°
(h) Response amplitude	1 mV to 10V peak
(i) Resetting control steps	0:5:10:20:50:100%
(j) Input	Isolated (earth and output)
(k) Output	Isolated (earth and input)
(l) Power supply	As for servo under test

RESTRICTED

RESTRICTED

TABLE 1 (Page 1)

HARMONIC RESPONSE TESTER COMPONENTS LIST

Circuit Ref.	Description	Patt. No.	Value	Tol. %	Rating
<u>Resistors</u>			<u>Ohms</u>		<u>Watts</u>
R1	Composition G-1	021-5281	2.2K	5	$\frac{1}{4}$
R2	"	021-6145	220K	"	"
R3	"	021-6965	1M	"	"
R4	"	021-6129	120K	"	"
R5	"	021-6951	27K	"	"
R6, R7, R8	"	021-6001	10K	"	"
R9	"	021-5211	1K	"	"
R10	"	021-5021	15	"	"
R11	"	021-6129	120K	"	"
R12	"	021-6962	10M	"	$\frac{1}{2}$
R13	"	021-0736	18K	1	$\frac{1}{8}$
R14	"	021-0721	1.8K	"	"
R15	"	021-0652	18J	"	"
R16	"	"	20	"	"
R17	"	021-6101	68K	5	$\frac{1}{4}$
R18	"	021-5341	6.8K	"	"
R19	"	021-6101	68K	"	"
R20	"	021-5271	1.8K	"	"
R21	"	021-6101	68K	"	"
R22	"	021-5341	6.8K	"	"
R23	"	021-5211	560	"	"
R24	"	021-6925	330K	"	"
R25	"	021-5341	6.8K	"	"
R26	Wire Wound	"	330	"	6
R27	Composition G-1	021-5271	1.8K	"	$\frac{1}{4}$
R28, 29	"	"	100	2	$\frac{1}{2}$
R30, 31, 32	Composition G-1	021-5520	920	"	$\frac{1}{4}$
R33, 34	"	021-5640	1K	"	"
R35, 36	"	021-6211	10K	"	"
R37, 38	"	021-5800	4.7K	"	"
R39, 40, 41	"	021-6450	100K	"	"
R42	"	021-5720	2.2K	"	"
R43	"	021-6350	39K	"	"
R44	"	021-6291	22K	"	"
R45, 46	"	021-6271	18K	"	"
R47	"	021-6370	4.7K	"	"
R48	"	021-5640	1K	"	"
R49	"	021-0778	10K	1	$\frac{1}{8}$
R50, 51	"	021-0727	2K	"	"
R52, 53, 54	"	021-0706	1K	"	"
R55	"	021-0790	15K	"	"
R56	"	021-0715	1.5K	"	"
R57	"	021-0706	1K	"	"
R58	"	021-0709	1.1K	"	"
R59	"	021-0778	10K	"	"
R60, 61	"	021-0727	2K	"	"
R62	"	021-0706	1K	"	"
R63, 64, 65	"	021-6211	10K	2	$\frac{1}{4}$
R66	"	021-5341	6.8K	"	"
R67	"	021-6251	15K	"	"
R68	"	021-5640	1K	"	"

RESTRICTED

RESTRICTED

TABLE 1 (Page 2)

HARMONIC RESPONSE TESTER

COMPONENTS LIST

Circuit Ref.	Description	Patt. No.	Value	Tol. $\pm\%$	Rating
<u>Resistors (contd.)</u>			<u>Ohms</u>		<u>Watts</u>
R69, 70	Composition G-1	021-6962	10M	5	$\frac{1}{2}$
R71, 72	"	021-6962	10M	"	"
R73, 74	"	021-6121	100K	"	$\frac{1}{4}$
R75, 76	"	021-5251	1.2K	"	"
R77, 78	"	021-6041	22K	"	"
R79, 80	"	021-5101	68	"	"
R81, 82	Wire Wound	021-5701	1.8K	2	$\frac{1}{2}$
R83, 84		A.P.52443	3		$\frac{1}{2}$
R85, 86	Composition G-1	021-5640	1K	2	$\frac{1}{4}$
R87, 88	"	021-5581	560	2	$\frac{1}{4}$
R89, 90	Wire Wound	024-5001	1	10	$\frac{1}{4}$
R91	Composition G-1	021-6211	10K	2	$\frac{1}{4}$
R92, 93	"	021-0849	100K	2	"
R94, 95	"	021-0849	100K	2	"
<u>Potentiometers</u>					
RV 1	RVC 15A	011-9467	50K	20	$\frac{1}{4}$
RV 2	Trimpotr.	972-7194	20K	10	$\frac{1}{2}$
RV 3	"		10K	10	"
RV 4	Log-potr.		25K		
RV 5	Trimpotr.		5K	10	$\frac{1}{2}$
RV 6	"		1K	10	$\frac{1}{2}$
RV 7	"		5K	10	$\frac{1}{2}$
RV 8			5		
RV 9	Trimpotr.		100	10	$\frac{1}{2}$
RV 10	RVW2	011-9861	5K	10	$\frac{1}{2}$
RV 11	"	011-9857	250	"	"
RV 12	"	011-9853	10	"	"
RV 13	RVC 15A	011-9468	100K	20	$\frac{1}{4}$
RV 14	Trimpotr.		100	10	$\frac{1}{2}$
RV 15	"		100	"	"
RV 16	RVW2	011-9853	10	10	$\frac{1}{2}$
RV 17	RVW8	027-2142	10K	"	1
<u>Capacitors</u>			<u>μF</u>		<u>Volts</u>
C1, 2	Electrolytic (TA) (Pellet)	012-0138	140	20	30
C3, 4	Electrolytic (TA)	014-5334	10		150
C5, 6	"	"	10		"
C7, 8, 9,			1		"
C10, 11	Electrolytic (TA)	014-5297	25		50
C12			0.1		
C13	Electrolytic (TA)	012-0138	140	20	30
C14		Z115571	1	25	350

RESTRICTED

RESTRICTED

TABLE 1 (Page 3)

HARMONIC RESPONSE TESTER

COMPONENTS LIST

Circuit Ref.	Description	Patt. No.	Value	Tol. %	Rating
<u>Capacitors (contd.)</u>			<u>μF</u>		<u>Volts</u>
C15		012-0600	0.05		250
C16, 17		Z116311	1		150
C18, 19		"	1		"
C20, 21	Electrolytic (TA)	Z145328	15		100
C22, 23	"	"	15		"
C24	Electrolytic (TA) (Pellet)	012-0138	3 x 140	20	30
C25	"	"	3 x 140	"	"
C26, 27	"	"	140	"	"
C28	"	"	2 x 140	"	"
<u>Diodes</u>					
D1, 2		000-4073			
D3, 4		"			
D5, 6		000-4074			
Meter	Rectifier-Test	"			
D7, 8	ZR11	037-2024			
D9, 10	"	"			
D11, 12	"	"			
D13, 14	"	"			
D15, 16	IS113	037-2000			
D17, 18	"	"			
D19, 20)	ZR21	037-2013			
D21, 22)					
<u>Meters</u>					
Amplitude	B.P.L. 6714/1	5000 Ω/V			
Phase	B.P.L. 8271/2	2010Ω			
Frequency	B.P.L. 8271/1	1800 Ω			
<u>Zener Diodes</u>					<u>Volts</u>
Z1		037-2392			9.1
Z2, 3		037-2203			6.8
Z4, 5		037-2205			8.2
Z6, 7, 8		037-2392			8.2
Z9, 10, 11		"			"
<u>Synchros etc.</u>					
T/F 11CT4B					
TX 11CX4B					
Motor 5UD/6662					
T.G. 18 FM/R					

RESTRICTED

RESTRICTED

TABLE 1 (Page 4)

HARMONIC RESPONSE TESTER

COMPONENTS LIST

Circuit Ref.	Description	Patt. No.	Value	Tol. %	Rating
<u>Transistors</u>				<u>Type</u>	
T1, 2	2S005	037-2111		Si	NPN
T3, 4	"	"		"	"
T5	0C205	037-2529		"	PNP
T6	0C29	037-2158		Ge	"
T7, 8	2S005	037-2111		Si	NPN
T9, 10	"	"		"	"
T11, 12	"	"		"	"
T13, 14	"	"		"	"
T15, 16	"	"		"	"
T17, 18	"	"		"	"
T19	"	"		"	"
T20	0C29	037-2158		Ge	PNP
T21	2S005	037-2111		Si	NPN
T22, 23	2S018	037-2116		"	"
T24, 25	2S005	037-2111		"	"
T26, 27	0C23	037-2100		Ge	PNP
T28, 29	0C77	037-2007		"	"
<u>Valves</u>					
V1	12AU7	CV4003			
V2, 3	ME1401	CV2269			
<u>Switches</u>				<u>Function</u>	
SW 1	D/P ON-OFF			Main Supply I/P. Frequency C.O.S. TR1 Primary Tap C.O.S. O/P Volts Level Run-Sweep	
SW 2	D/P 2 Posn.				
SW 3	CS/2P/11/1B	Painton			
SW 4, 5, 6	CS/1P/10/1B	"			
SW 7	S/P 3 Posn.			Amplitude Range Cal. - Run - Dump	
SW 8	S1450/4/AAAA/A	Ardente			
SW 9	3/P 3 Posn.				
SW 10	S1450/6/AAAA/A	Ardente			
SW 11	S1450/6/BBBB/A	Ardente		Test 1 Test 2	
SW 12	S1450/6/BB00/A	"			
<u>Transformers</u>				<u>Function</u>	
TR1	RPC 573			Signal Output 90 r.m.s./0-10 Vp. High Impedance Isolating. Reset Amplifier Driver. " " Push Pull O/P. Reference Voltage. Stab. Power Supply 2(20.5V) 1(25V)	
TR2	RPC 588				
TR3	RPC 593				
TR4	RPC 589				
TR5	RPC 578				
TR6	RPC 597				

REPORT NO. 2383/3384/1


RESTRICTED

RESTRICTED

FIG. 1.

HARMONIC RESPONSE TESTER.

LABORATORY PROTOTYPE MODEL.




RESTRICTED

FIG. 2.

HARMONIC RESPONSE TESTER

SCHEMATIC DIAGRAM



SIGNAL GENERATOR




RESTRICTED


FIG. 3.

HARMONIC RESPONSE TESTER

SIGNAL GENERATOR



2



RESTRICTED

HARMONIC RESPONSE TESTER

RESET AMPLIFIER

1






FIG. 4.

RESET AMPLIFIER



HARMONIC RESPONSE

AMPLITUDE AMPLIFIER




RESTRICTED

FIG. 5

RESPONSE TESTER.
VIDEO AMPLIFIER

2




REPORT No. 2383/3384/1

HARMONIC RESPONSE TESTER

PHASE MEASURING UNIT

1




RESTRICTED

FIG. 6.

HARMONIC RESPONSE TESTER

PHASE MEASURING UNIT

2



HARMONIC RESPONSE TESTER

POWER SUPPLY UNIT





FIG. 7.

POWER SUPPLY UNIT





*Information Centre
Knowledge Services*
[dstl] Porton Down,
Salisbury
Wilts
SP4 0JQ
22060-6218
Tel: 01980-613753
Fax 01980-613970

Defense Technical Information Center (DTIC)
8725 John J. Kingman Road, Suit 0944
Fort Belvoir, VA 22060-6218
U.S.A.

AD#: AD337352

Date of Search: 31 July 2008

Record Summary: ADM 227/1797

Title: Harmonic response tester

Availability Open Document, Open Description, Normal Closure before FOI Act: 30 years

Former reference (Department) Report No. 2383

Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.

The document has been released under the 30 year rule.

(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

This document may be treated as UNLIMITED.